


ALUMINIUM BANNER FLAGPOLE

In this model, the banner flagpole comes with no halyard.

The flagpole is provided with a fixed horizontal rotary arm, which keeps the flag always legible. The flagpole needs to be laid on the ground before the flag can be fitted or removed.

The price includes: flagpole, grey flat ball finial, rotary head, jib (banner), weight, clamps (x5), mounting anchor or fixing sleeve. Depending on their height, the aluminium flagpoles are made up of two, three or four aluminium tubes that are pushed together using sleeves and aluminium rings. The flagpoles are installed in a concrete base using a mounting hinge or fixing sleeve. The hinge makes the installation easier and makes it possible to lay the flagpole on the ground, e.g. during maintenance. A system of screws makes it possible to adjust the vertical position of the flagpole.

Our flagpoles are available in any RAL colour.



Available accessories

FINIALS



LARGE GREY BALL FINIAL*

SMALL GREY BALL FINIAL

SILVER DROP FINIAL**

HEAD

*also available in silver and gold colours

**also available in white and gold colours

FITTING AND FLYING THE FLAG




CLAMPS

WEIGHT

SWIVEL

BASE



HINGED BASE PLATE
(LEG+ANCHOR)

SLEEVE

PORTABLE BASE

BASE PLATE MASK

Height (m)	6	7	8	9	10	11	12
Number of sections (pcs)	2	2	2	2	3	3	3
Section diameter (mm)	82.5/67.5	82.5/67.5	82.5/67.5	82.5/67.5	98.5/82.5/67.5	98.5/82.5/67.5	98.5/82.5/67.5
Wall thickness (mm)	3.5/3	3.5/3	3.5/3	3.5/3	4/3.5/3	4/3.5/3	4/3.5/3
Net weight without accessories (kg)	13	15.6	18.2	21.5	25.7	29.5	31.4
Recommended maximum flag dimensions (m)	150×400	150×400	150×500	120×500	150×500	150×600	150×700

AGRA - FLAGPOLES, ul. Kolejowa 3, 95-082 Dobroń, Poland

W: www.agra-dobron.pl, E: agra@agra-dobron.pl

P: +48 43-67-72-601, +48 43-67-72-017, +48 43-67-12-076, F: +48 43 67-72-028