

STANDARD GLAS FIBRE FLAGPOLE

In this model, the halyard runs outside the flagpole and is attached to a cleat mounted at approx. 1.5m above ground level. The price includes: flagpole, white flat ball finial, rotary head, halyard, cleat, mounting anchor.

The glass fibre flagpoles are made from a single component (tube), which is tapered towards the top. The flagpoles are installed in a concrete base using a mounting hinge. The hinge makes the installation easier and enables to lay the flagpole on the ground, e.g. during maintenance. A system of screws makes it possible to adjust the vertical position of the flagpole.

Our flagpoles are available in any RAL colour.



Available accessories

FINIALS

			
1	2	3	4
LARGE WHITE BALL FINIAL*	SMALL WHITE BALL FINIAL	SILVER DROP FINIAL**	HEAD

*also available in silver and gold colours

**also available in white and gold colours

FITTING AND FLYING THE FLAG

	
1	2
CLEAT	HALYARD

BASE

		
1	2	3
HINGED BASE PLATE (LEG+ANCHOR)	PORTABLE BASE	BASE PLATE MASK

Height (m)	6	7	8	9	10	11	12
Diameter at base (mm)	125	125	125	125	145	145	145
Diameter at top (mm)	65	65	65	65	65	65	65
Net weight without accessories (kg)	10.8	14.2	15.2	19.9	21.8	25.8	29.4
Recommended maximum flag dimensions (m)	150x400	150x400	150x500	150x500	150x600	150x600	150x700